

## Safety and action boots for fire-fighting units

### ZGF 0001-A



**Name:** ZGF 0001-A  
**Sizes assortment:** 39-46  
**Specification:** EN 345 SB P WRU CI FP

**Description:**

**FIREFIGHTER ACTION SEMI-TOP BOOT**

**Upper:**

- Various versions in genuine "Stop Fire" full grain leather complying with the EN 345 – 2FP standard
- Water and oil resistant upper (penetration and absorption)
- 2 side zips for quickly and easy fastening

**Construction:**

- Thermal insulation against cold
- Steel toe cap resisting up to 200 Joules
- Goodyear welted construction (Norwegian lasting)

**Sole:**

- Steel midsole
- Sole in neoprene and rubber

### ZGF 0001-B



**Name:** ZGF 0001-B  
**Sizes assortment:** 39-46  
**Specification:** EN 347 HI WRU ORO P

**Description:**

**RANGERS FIREFIGHTER ACTION SEMI-TOP BOOT**

**Upper:**

- Various versions in genuine full grain leather
- Water and oil resistant upper (penetration and absorption)
- 2 side zips for quickly and easy fastening

**Construction:**

- Thermal insulation against heat
- Applying with the specifications of DDSC NIT 310
- Goodyear welted construction (Norwegian lasting)

**Sole:**

- Steel midsole
- Sole in neoprene and rubber

### ZMF PRESTIGE-A



**Name:** ZMF PRESTIGE-A  
**Sizes assortment:** 35-49  
**Specification:** EN 347

**Description:**

**All-purpose low shoes suitable especially for work and different kinds of leisure activities and sports - PRESTIGE type**

- Great comfort during walking and standing is provided by using high quality materials - leather upper and PU sole
- Thanks to their characteristics and durability they were certified as working shoes for standard working conditions

**Prestige high-tops** combine the quality of Prestige with better ankle support

### ZMF PRESTIGE-B



**Name:** ZMF PRESTIGE-B  
**Sizes assortment:** 35-49  
**Specification:** EN 347

**Description:**

**All-purpose ankle boots suitable especially for work and different kinds of leisure activities and sports - PRESTIGE type**

- Great comfort during walking and standing is provided by using high quality materials - leather upper and PU sole
- Thanks to their characteristics and durability they were certified as working shoes for standard working conditions

**Prestige high-tops** combine the quality

of Prestige with better ankle support

## ZNF FIRESTAR-A



**Name:** ZNF FIRESTAR-A  
**Sizes assortment:** 38-48  
**Specification:** EN 15009:2006 HI

### Description:

#### Fire-fighting rubber rescue action top boot

- Rubber compounds containing fire extinguishing additives
- Mixed cotton fabric lining giving increased abrasion resistance
- Sock lining increasing antistatic properties and enhancing comfort
- Extended leg for easy tucking-in of working trousers
- Antistatic construction
- Outsole resistant to oil, fuels, acids and temperature to 250°C
- Steel anti-perforation insert
- Anatomic replaceable innersole washable in water 40°C
- Absorbing treads energy in heel
- Boot stiffened with Rubber toe puff
- Height 33 cm
- This boots are certified and approved to be used by fire-fighting rescue crews

## ZNF FIRESTAR-B



**Name:** ZNF FIRESTAR-B  
**Sizes assortment:** 38-48  
**Specification:** EN 15009:2006 HI

### Description:

#### Fire-fighting rubber rescue action top boot

- Rubber compounds containing fire extinguishing additives
- Mixed cotton fabric lining giving increased abrasion resistance
- Sock lining increasing antistatic properties and enhancing comfort
- Extended leg for easy tucking-in of working trousers
- Antistatic construction
- Outsole resistant to oil, fuels, acids and temperature to 250°C
- Steel anti-perforation insert
- Anatomic replaceable innersole washable in water 40°C
- Absorbing treads energy in heel
- Boot stiffened with Rubber toe puff
- Height 33 cm
- This boots are certified and approved to be used by fire-fighting rescue crews

## ZNF FIRESTAR-C



**Name:** ZNF FIRESTAR-C  
**Sizes assortment:** 38-48  
**Specification:** EN 15009:2006 HI

### Description:

#### Fire-fighting rubber rescue action top boot

- Rubber compounds containing fire extinguishing additives
- Mixed cotton fabric lining giving increased abrasion resistance
- Sock lining increasing antistatic properties and enhancing comfort
- Extended leg for easy tucking-in of working trousers
- Antistatic construction
- Outsole resistant to oil, fuels, acids and temperature to 250°C
- Steel anti-perforation insert
- Anatomic replaceable innersole washable in water 40°C
- Absorbing treads energy in heel
- Boot stiffened with Rubber toe puff
- Height 33 cm
- This boots are certified and approved to be used by fire-fighting rescue crews

## ZPF ZEMAN 01-A



**Name:** ZPF ZEMAN 01-A  
**Sizes assortment:** 39-48  
**Specification:** EN 345 S3 HRO

### Description:

#### Fire-fighting action high boot with safekeeping spike special PU cap

**Upper:** Full grain hydrophobized leather, safekeeping spike special PU thickness, padded collar  
**Color:** Black  
**Lining:** DRILEX+WINDTEX giving comfort climate  
**Sock lining:** Anatomic replaceable innersole washable in water 40°C, absorbing tread energy in heel  
**Construction:** Antistatic construction  
**Safety feature:** Steel toe cap impact resistant up to 200 J  
**Steel mid plate:** Puncture resistant up to 1100 N  
**Sole:** Nitrile rubber outsole with steel anti-perforation insert, resistant to oil, fuels, acids and temperature 300°C

**This boots are certified and approved to be used by fire-fighting rescue crews**

**ZPF ZEMAN 01-B**



**Name:** ZPF ZEMAN 01-B  
**Sizes assortment:** 39-48  
**Specification:** EN 345 S3 HRO

**Description:**

**Fire-fighting action high boot with safekeeping spike special PU cap**

**Upper:** Full grain hydrophobized leather, safekeeping spike special PU thickness, padded collar  
**Color:** Black  
**Lining:** Vellutino PA with high abrasion resistant  
**Sock lining:** Anatomic replaceable innersole washable in water 40°C, absorbing tread energy in heel  
**Construction:** Antistatic construction  
**Tension insole:** Antistatic Texon  
**Safety feature:** Steel toe cap impact resistant up to 200 J  
**Steel mid plate:** Puncture resistant up to 1100 N  
**Sole:** Nitrile rubber outsole with steel anti-perforation insert, resistant to oil, fuels, acids and temperature 300°C

**This boots are certified and approved to be used by fire-fighting rescue troops**

**ZPF ZEMAN 01-C**



**Name:** ZPF ZEMAN 01-C  
**Sizes assortment:** 39-48  
**Specification:** EN 345 S3 HRO

**Description:**

**Fire-fighting action high boot, increasing 6 cm with safekeeping spike special PU cap**

**Upper:** Full grain hydrophobized leather, safekeeping spike special PU thickness, padded collar  
**Color:** Black  
**Lining:** DRILEX+WINDTEX giving comfort climate  
**Sock lining:** Anatomic replaceable innersole washable in water 40°C, absorbing tread energy in heel  
**Construction:** Antistatic construction  
**Safety feature:** Steel toe cap impact resistant up to 200 J  
**Steel mid plate:** Puncture resistant up to 1100 N  
**Sole:** Nitrile rubber outsole with steel anti-perforation insert, resistant to oil, fuels, acids and temperature 300°C

**This boots are certified and approved to be used by fire-fighting rescue crews**

**ZPF ZEMAN 02-A**



**Name:** ZPF ZEMAN 02-A  
**Sizes assortment:** 39-48  
**Specification:** EN 345 S3 HRO


**Description:**

**Fire-fighting action top boot with fast-action lacing and safekeeping spike special PU cap**

**Upper:** Full grain hydrophobized leather, safekeeping spike special PU thickness, padded collar  
**Color:** Black  
**Lining:** DRILEX+WINDTEX giving comfort climate  
**Sock lining:** Anatomic replaceable innersole washable in water 40°C, absorbing tread energy in heel  
**Construction:** Antistatic construction  
**Safety feature:** Steel toe cap impact resistant up to 200 J  
**Steel mid plate:** Puncture resistant up to 1100 N  
**Sole:** Nitrile rubber outsole with steel anti-perforation insert, resistant to oil, fuels, acids and temperature 300°C

**This boots are certified and approved to be used by fire-fighting rescue crews**

**ZPF ZEMAN 02-B**



**Name:** ZPF ZEMAN 02-B  
**Sizes assortment:** 39-48  
**Specification:** EN 345 S3 HRO

**Description:**

**Fire-fighting action top boot with fast-action lacing and safekeeping spike special PU cap**

**Upper:** Full grain hydrophobized leather, safekeeping spike special PU thickness, padded collar  
**Color:** Black  
**Lining:** Vellutino PA with high abrasion resistant  
**Sock lining:** Anatomic replaceable innersole washable in water 40°C, absorbing tread energy in heel  
**Construction:** Antistatic construction  
**Tension insole:** Antistatic Texon  
**Safety feature:** Steel toe cap impact resistant up to 200 J  
**Steel mid plate:** Puncture resistant up to 1100 N  
**Sole:** Nitrile rubber outsole with steel anti-perforation insert, resistant to oil, fuels, acids and temperature 300°C

**This boots are certified and approved to be used by fire-fighting rescue crews**

## ZPF ZEMAN 03-A



**Name:** ZPF ZEMAN 03-A  
**Sizes assortment:** 39-48  
**Specification:** EN 347-1 O2 HI HRO WR

### Description:

### Fire-fighting action top boot with laces - WILDLAND type

**Upper:** Full grain hydrophobized leather, safekeeping spike special PU thickness, padded collar  
**Color:** Black  
**Lining:** Drilex with membrane + Thinsulate  
**Sock lining:** Anatomic replaceable innersole washable in water 40°C, absorbing tread energy in heel  
**Construction:** Antistatic construction  
**Safety feature:** Thermoplastic toe cap  
**Sole:** Nitrile rubber outsole, resistant to oil, fuels, acids and temperature 300°C

**This boots are certified and approved to be used by fire-fighting rescue crews**

## ZSF 10 RIGGER-S3



**Name:** ZSF 10 RIGGER-S3  
**Sizes assortment:** 39-47  
**Specification:** EN 345 S3 HRO

### Description:

### High boot - type Rigger (S3)

**Upper:** Buffalo DIN full grain leather upper, color black.  
**Lining:** Cambrelle lining at quarter.  
**Sole:** Nitrile rubber/PU sole.

**Boot with steel toe cap and antiperforation steel midsole, boot fit for training firefighting troops**

## ZSF FIRESTAR-D



**Name:** ZSF FIRESTAR-D  
**Sizes assortment:** 38-47  
**Specification:** EN 345 S5

### Description:

### Fire-fighting rubber rescue action top boot

- Rubber compounds containing fire extinguishing additives
- Mixed cotton fabric lining giving increased abrasion resistance
- Sock lining increasing antistatic properties and enhancing comfort
- Extended leg for easy tucking-in of working trousers
- Antistatic construction
- Outsole resistant to oil, fuels, acids and temperature to 250°C
- Steel anti-perforation insert
- Anatomic replaceable innersole washable in water 40°C
- Absorbing treads energy in heel
- Boot stiffened with Rubber toe puff
- Height 33 cm
- This boots are certified and approved to be used by fire-fighting rescue crews

## ZUF ZEMAN 02-C



**Name:** ZUF ZEMAN 02-C  
**Sizes assortment:** 39-48  
**Specification:** EN 345 S3 HRO

### Description:

### Fire-fighting action top boot with side velcro, hydrophobized leather and safekeeping instep

**Upper:** Full grain hydrophobized leather, safekeeping spike special PU thickness, padded collar  
**Color:** Black  
**Lining:** DRILEX+WINDTEX giving comfort climate  
**Sock lining:** Anatomic replaceable innersole washable in water 40°C, absorbing tread energy in heel  
**Construction:** Antistatic construction  
**Safety feature:** Steel toe cap impact resistant up to 200 J  
**Steel mid plate:** Puncture resistant up to 1100 N  
**Sole:** Nitrile rubber outsole with steel anti-perforation insert, resistant to oil, fuels, acids and temperature 300°C

**This boots are certified and approved to be used by fire-fighting rescue and motorcycle troops**

## ZZF G001



**Name:** ZZF G001  
**Sizes assortment:** M,L  
**Specification:** NFPA, GA7-2004, EN 659.96

### Description:

#### Fire fighter's gloves

Fire fighter's gloves used during structural fire fighting operations including rescue of victim from fires, and emergency operation where sharp or rough surface are likely to be encountered such as victim extrications.

**1.Outer layer:** The material is made from NOMEX. It enjoys the ability of flame resistant, oil proof, electrical insulation. It also has good resistance to acids and alkalis.

**2.Moisture barrier:** GORE-TEX, the material could stop water passing through to the firefighter's personal clothing while allowing perspiration and heat to escape to the outside atmosphere.

**3.Thermal Barrier:** It used the no-woven felt made of ARAMID. To thermal barrier, flame resistant, anti heat radiation.

**4.Comfortable layer:** Flame resistant cotton.

#### In accordance with:

American standard NFPA

Chinese Standard GA7-2004

EN 420: 94. General requirements for protective gloves

EN 388: 94. Protective gloves for mechanical hazards

EN 407: 94. Protective gloves for thermal hazards heat and/or fire

EN 659: 96. Protective gloves for firefighters

EN 388



EN 407



EN 659



## ZZF ZEMAN 02-D



**Name:** ZZF ZEMAN 02-D  
**Sizes assortment:** 39-48  
**Specification:** EN 345 S3 HRO

### Description:

#### Fire-fighting action top boot with fast-action lacing and safekeeping spike special PU cap

**Upper:** Full grain hydrophobized leather, safekeeping spike special PU thickness, padded collar

**Color:** Black

**Lining:** DRILEX+WINDTEX giving comfort climate

**Sock lining:** Anatomic replaceable innersole washable in water 40°C, absorbing tread energy in heel

**Construction:** Antistatic construction

**Safety feature:** Steel toe cap impact resistant up to 200 J

**Steel mid plate:** Puncture resistant up to 1100 N

**Sole:** Nitrile rubber outsole with steel anti-perforation insert, resistant to oil, fuels, acids and temperature 300°C

**This boots are certified and approved to be used by fire-fighting rescue crews**

This page was generated at **Tuesday, May 13, 2008** from actual Product Catalog database on the web.

#### Contact information:

Technogroup s.r.o.  
687 42 Osvětimany 385  
CZECH REPUBLIC

**WWW:** <http://www.zeman.cz>

**E-mail:** [info@zeman.cz](mailto:info@zeman.cz)

**Fax:** +420-572-594 353